

CORKIA SUPRA

LCF3400LX3

Taric 9405114090



Technical Standards

EN-60598-1, EN-60598-2-22, EN-62034

Certifications




Functional Specifications

	Self-Contained
	Control system: AutoTest
	AutoTest: Yes
	Type: Non-maintained
	Supply: 230V 50Hz<0.6W
	Non-maintained mode consumption: 0.6 W
	Emergency: 420 lm
	Duration: 3 h Battery: 6.4V-4.0Ah LiFePO ₄
	Charging time: 12 h

Mechanical and Aesthetic Specifications

	Mounting: Ceiling/Wall Surface
	Insulation: Class II
	IP20
	IK04
	Lamp: 1 x LED 4W
	LED color temperature: 4000 K
	Body material: Cork
	Finish: Brown Cork
	Diffuser / Optics: Polycarbonate Anti-panic Lens
	Working temperature: 0 / 40 °C
	Suitable for flammable surface: Yes



CORKIA SUPRA LCF3400LX3

Installation characteristics

Installation type:

- Ceiling/Wall surface.

Possibility of connection with:

- Surface conduit wiring.



Operating characteristics

The luminaire has a built-in button, which allows:

- Put on Standby without power supply.

Microprocessor controlled luminaire that performs periodic and automatic tests.








Functional test every **7 days**.




Duration test every **365 days**.

The test result is shown in the status indicator LEDs.

The luminaire has status LEDs, which indicates:

-  Green on: correct operation
-  Orange on: incorrect battery or duration
-  Both leds off: no power supply or total failure of the luminaire
-  Green flashing: test in progress
-  Orange flashing: functional failure

Spacing table



h	a	b	c	d
2 m	6,3 m	12,0 m	6,3 m	12,5 m
2.5 m	7,5 m	13,5 m	7,2 m	14,0 m
3 m	8,4 m	15,5 m	8,1 m	15,5 m
4 m	9,0 m	18,5 m	9,0 m	18,5 m
5 m	7,8 m	21,5 m	7,8 m	21,5 m


Spacing data calculated with no reflections and a maintenance factor of 0.9.

Compliant with the updated standard EN-1838:2024.

Minimum illuminance of 0.5 lux (anti-panic calculation).

The calculation of spacing distances is carried out considering the height of the light emission point, without taking into account the dimensions of the luminaire.

Photometric guide



CORKIA SUPRA LCF3400LX3

Weight (kg)



Product weight:

0.28 kg

Boxed product weight:

0.31 kg

Weight of box of 15 units:

4.89 kg



Dimensions (mm)

