

# CORKIA SUPRA

## LCF3403LX3

Taric 9405114090



### Technical Standards

EN-60598-1, EN-60598-2-22, EN-62034

### Certifications



### Functional Specifications

	Self-Contained
	Control system: AutoTest
	AutoTest: Yes
	Type: Non-maintained
	Supply: 230V 50Hz<0.6W
	Non-maintained mode consumption: 0.6 W
	Emergency: 380 lm
	Duration: 3 h Battery: 6.4V-4.0Ah LiFePO <sub>4</sub>
	Charging time: 12 h

### Mechanical and Aesthetic Specifications

	Mounting: Ceiling Surface
	Insulation: Class II
	IP20
	IK04
	Lamp: 1 x LED 4W
	LED color temperature: 4000 K
	Body material: Cork
	Finish: Brown Cork
	Diffuser / Optics: Corner Polycarbonate Lens
	Working temperature: 0 / 40 °C
	Suitable for flammable surface: Yes



# CORKIA SUPRA LCF3403LX3

## Installation characteristics

Installation type:

- Ceiling/Wall surface.

Possibility of connection with:

- Surface conduit wiring.

Especially for changes of direction in corridors



## Operating characteristics

The luminaire has a built-in button, which allows:

- Put on Standby without power supply.

Microprocessor controlled luminaire that performs periodic and automatic tests.








Functional test every **7 days**.




Duration test every **365 days**.

The test result is shown in the status indicator LEDs.

The luminaire has status LEDs, which indicates:

- |   |  |  |
|---|--|--|
|  Green on: correct operation      |  Orange on: incorrect battery or duration |  Both leds off: no power supply or total failure of the luminaire |
|  Green flashing: test in progress |  Orange flashing: functional failure      |  |

## Spacing table




h	a	b
<b>2 m</b>	4,4 m	16,3 m
<b>2.5 m</b>	4,9 m	18,2 m
<b>3 m</b>	5,3 m	19,3 m
<b>4 m</b>	5,7 m	20,5 m
<b>5 m</b>	5,8 m	18,4 m

Spacing data calculated with no reflections and a maintenance factor of 0.9.  
Compliant with the updated standard EN-1838:2024.

Minimum illuminance of 1 lux over a 1 m wide evacuation path.

The calculation of spacing distances is carried out considering the height of the light emission point, without taking into account the dimensions of the luminaire.

## Photometric guide



# CORKIA SUPRA LCF3403LX3

## Weight (kg)



Product weight:

0.28 kg

Boxed product weight:

0.31 kg

Weight of box of 15 units:

4.89 kg



## Dimensions (mm)

