

CORKIA SPACE

LCR3403LX3


Taric 9405114090



Technical Standards

EN-60598-1, EN-60598-2-22, EN-62034

Certifications



Functional Specifications

Mechanical and Aesthetic Specifications

	Self-Contained
	Control system: AutoTest
	AutoTest: Yes
	Type: Non-maintained
	Supply: 230V 50Hz<0.6W
	Non-maintained mode consumption: 0.6 W
	Emergency: 380 lm
	Duration: 3 h Battery: 6.4V-4.0Ah LiFePO ₄
	Charging time: 12 h

	Mounting: Ceiling Recessed
	Insulation: Class II
	IP44
	IK04
	Lamp: 1 x LED 4W
	LED color temperature: 4000 K
	Body material: Cork
	Finish: Brown Cork
	Diffuser / Optics: Corner Polycarbonate Lens
	Working temperature: 0 / 40 °C
	Suitable for flammable surface: Yes



CORKIA SPACE LCR3403LX3

Installation characteristics

Luminaires made up of a spotlight + electrical equipment + batteries

Installation type:

- Recessed ceiling.

Optics designed for changes of direction in corridors

Double spring clips installation method.

Cables between different halogen-free elements.



Operating characteristics

The luminaire has a built-in button, which allows:

- Put on Standby without power supply.

Microprocessor controlled luminaire that performs periodic and automatic tests.



Functional test every **7 days**.




Duration test every **365 days**.

The test result is shown in the status indicator LEDs.

The luminaire has status LEDs, which indicates:

- | | | | | | |
|--|----------------------------------|--|--|--|--|
| | Green on: correct operation | | Orange on: incorrect battery or duration | | Both leds off: no power supply or total failure of the luminaire |
| | Green flashing: test in progress | | Orange flashing: functional failure | | |

Spacing table



h	a	b
2 m	4,4 m	16,7 m
2.5 m	4,9 m	18,6 m
3 m	5,3 m	19,8 m
4 m	5,8 m	21,4 m
5 m	5,9 m	18,4 m


Spacing data calculated with no reflections and a maintenance factor of 0.9.

Compliant with the updated standard EN-1838:2024.

Minimum illuminance of 1 lux over a 1 m wide evacuation path.

The calculation of spacing distances is carried out considering the height of the light emission point, without taking into account the dimensions of the luminaire.

Photometric guide



CORKIA SPACE LCR3403LX3

Weight (kg)



Product weight:

0.28 kg

Boxed product weight:

0.31 kg

Weight of box of 15 units:

4.89 kg

Dimensions (mm)

