

SATURNO LIGHTING

LSIPC2200A

Taric 9405114090



Technical Standards

EN-60598-1, EN-60079-0, EN-60079-1, EN-60079-31,
 EN-62386

Certifications



ClassNK

Functional Specifications

	Illumination
	ATEX Zone 1/Zone 21/Ex db IIC T6 Gb/Ex tb IIIC T85°C Db
	Control system: DALI2
	Data Bus: Yes
	Supply: 220-240V 50-60Hz<20W / 220-240Vdc<20W
	Power factor: 95%
	Maintained mode consumption: 20,0 W
	Mains: 2600 lm

Mechanical and Aesthetic Specifications

	Mounting: Ceiling/Wall Surface
	Insulation: ClassI
	IP66
	IK10
	Lamp: 1 X LED 16W
	LED color temperature: 4000 K
	Body material: Aluminum
	Finish: Yellow RAL1007
	Diffuser / Optics: Transparent Polycarbonate
	Working temperature: -20 / 50 °C
	Suitable for flammable surface: Yes



SATURNO LIGHTING LSIPC2200A

Installation characteristics

Electrical connection by 5-pole + T connector for cable up to 2.5 mm².

Installation type:

- Ceiling/Wall surface with clamping flanges.
- Suspended roof, with eyebolt.

Possibility of connection with:

- Surface conduit wiring.

Two 3/4" NPT entries for cable glands (not included), one of which is provided with a plug.

Tubular diffuser:

- Borosilicate glass, E1 (7mm thick) E2/E3 (9mm thick)
- Polycarbonate, UV protected. 3mm thick.

Casting & connections:

- Aluminum injection
- Manufactured from marine grade aluminum alloy copper free
- Yellow RAL-1003 polyurethane paint
- Explosion proof O-ring.
- 2 entries 3/4" NPT for cable glands (not included)
- 1 plug supplied
- Electric connection through 5P+T 2,5 mm² terminal block
- Suitable for installation on flammable surfaces



Operating characteristics

Valid to be supply in the following ways:

- Directly at rated voltage.

Accessories



ZWEBDALI2
CENTRAL DALI2



BRD001
ACC. FIXATION FLANGE SATURNO




CAM001
RING BOLT FOR PENDANT MOUNTING



PSA001
ACC. CABLE GLANDS SATURNO

SATURNO LIGHTING LSIPC2200A

Photometric guide



Weight (kg)



Product weight:

6.15 kg

Boxed product weight:

6.83 kg

Dimensions (mm)

