

ZEMPER

THE EMERGENCY LIGHTING SPECIALIST

Lighting in ATEX Zones



ClassNK



SATURNO

Zone 1/21 - 2/22

Explosion Proof Fittings ATEX



ClassNK







WORLD STANDARDS



IECEx (International Scheme)

The IECEx scheme is an international certificate of conformance for products used in a hazardous area.

This scheme provides:

- A single certification of conformity for manufacturers to comply that includes:
 - Testing and assessment of products to a standard including a full test report.
 - Ongoing surveillance of manufacturers premises.
- A fast-track process for countries where regulations still require the issuing of national Ex certificates or approvals.

ClassNK

Class NK works to ensure maritime safety and protect the marine environment.

It provides classification and technical services to roughly 20% of the world's commercial fleet.

Body: Marine grade Aluminium (LM6).



The ATEX European Directives 94/9/EC

ATEX requires employers to eliminate or control risks from dangerous substances and to classify areas where explosive atmospheres may occur into zones, as laid down in regulations. ATEX Directives are designed to protect employees, the public and the environment from accidents owing to explosive atmospheres and since July 1st 2006 all existing sites, as well as new sites, must be fully ATEX compliant.

The ATEX directive 2014/34/EU applies to end users. These directives compliment each other, but have different purposes. ATEX100A covers both electrical and non-electrical products intended for use in hazardous areas, including mechanical equipment.

Any product sold within the European Union designed for use in explosive atmospheres must be ATEX certified and bear the ATEX marking in conjunction with CE marking. The objective is to facilitate the movement of goods within the EU.



APPLICATION AREAS
EQUIPMENT CATEGORIES
EQUIPMENT PROTECTION LEVEL

The following chart shows the designated areas of use of equipment and components according to equipment group and equipment category/equipment protection level.

HAZARDOUS AREA

Conditions and subdivisions			Required marking on the usable equipment			
Flammable materials	Temporary behaviour of explosive atmosphere	Classification of hazardous areas	Equipment group as defined in directive 2014/34/EC	Equipment category as defined in directive 2014/34/EC	Equipment group as defined in IEC/EN 60079-0	Equipment protection level (EPL) as defined in IEC/EN 60079-0
Gases Vapours	Is present continuously or for long periods or frequently	Zone 0	II	1G	II	Ga
	Arises in normal operation occasionally	Zone 1	II	2G or 1G	II	Gb or Ga
	Is not likely to arise in normal operation, or if it does, will persist for a short time only	Zone 2	II	3G or 2G or 1G	II	Gc or Gb or Ga
Dusts	Is present in the form of a cloud continuously, or for long periods or frequently	Zone 20	II	1D	III	Da
	Occasionally develops into a cloud during normal operation	Zone 21	II	2D or 1D	III	Db or Da
	Is not likely to develop into a cloud during normal operation, or if it does, for a short time only	Zone 22	II	3D or 2D or 1D	III	Dc or Db or Da
Methane Carbon dust	Operation where there is a risk of explosion	-	II	M1	I	Ma
	Disconnection where there is a risk of explosion	-	I	M2 or M1	I	Mb or Ma



EMERGENCY LIGHTING - GENERAL DATA

- Led driver with AutoTest function as per IEC32034
- High temperature LiFePO₄ cells
- 20 hours charging to obtain the nominal duration
- Electronic multi-level charge system
- Deep discharge protection
- Switch ON / OFF connection is available for maintained luminaires.
- Status indication bi-colour LED: Green Ok - Red: Fault

Testing

- Commissioning test is carried out automatically after permanent connection of the supply for 5 days.
- Functional test is carried out for 5 seconds on a weekly basis.
- Duration test is carried out yearly to check the capacity of the batteries



SATURNO EXPLOSIONPROOF FEATURES

Approvals and Certifications

- Zone 1/2 / Zone 21/22
- Ex db IIC T6 Gb
- Ex tb IIIC T85 °C Db
- IK protection degree
PC E1, E2, E3 :IK10
Glass E1, E2: IK07 / E3: IK09
- IP66
- Class: I

Technical information

- Electronic driver: 220 - 240 V 50/60 Hz
- Power factor: 0.95
- Set of LED modules with opal cover diffuser:
 - Color temperature 4000 °K (6500 °K under request)
 - CRI > 80

Operation temperature:

- Glass diffuser (E1, E2, E3):
- Lighting working temperature -20 °C to +55 °C
 - Emergency working temperature: 0°C to +50°C

Polycarbonate diffuser (E1, E2, E3):

- Lighting working temperature: -20 °C to +50 °C
- Emergency working temperature: 0 °C to +50 °C

Standards

- Approved to:**
- EN 60079-0: (General requirements)
 - EN 60079-1: (Flameproof enclosure "d")
 - EN 60079-31: (Enclosure "t")

- EC Type examination:** · Directive: 2014/34/EU

- Certificated:** · Notified Body: INERIS n°0080



Enclosure general data

- Tubular diffuser:**
- Borosilicate glass, E1: 7 mm E2/ E3 9 mm
 - Polycarbonate, UV protected. 3 mm thick

Casting & connections:

- Marine Grade Aluminium (LM6)
- Yellow RAL-1003 / Polyurethane paint
- Explosion proof O-ring
- 2 entries 3/4" NPT for cable glands (not included)
- 1 ATEX plug supplied
- Electric connection through 5P+T 2.5 mm² terminal block
- Suitable for installation on flammable surfaces

MARKING EXAMPLE IN ACCORDANCE WITH DIRECTIVE 2014/34/EU, EN AND IEC STANDARDS (IEC/EN 60079-0 ET SEQ.)




INFORMATION SPECIFIC TO EXPLOSION PROTECTION (MARKING)

ATEX directive/EN standards

- | | |
|---|---|
| 1 Conformity mark (CE) | 5 Equipment group II - other areas (non-mining)
Equipment category 2 - gases/vapours G,
suitable for Zones 1 and 2 - dusts D,
suitable for Zones 21 and 22 |
| 2 Identification number of the notified body which
-where required- certified the QA system or examined
the products (Category 1 and 2) | 6 Certificate of conformity (*) |
| 3 Ex mark | 7 IP Protection degree
TEMP: Temperature Range |
| 4 EC-type examination certification | |

IEC standards

* Certificate of Conformity





SATURNO



Ex db IIC T6 Gb
Ex tb IIIC T85°C Db

IP66 **IK07 - IK10**

SPECIFICATION

Wall	Surface	✓
Ceiling	Surface	✓

Envelope:
Marine Grade Aluminium (LM6)

Diffuser: Borosilicate glass / Polycarbonate

IP66

IK protection degree

- PC E1, E2, E3: IK10
- Glass E1, E2: IK07 / E3: IK09

Lm

Lighting Luminous range: 1 250 lm - 11 750 lm
Emergency Luminous range: 70 lm - 850 lm



Duration: 1 - 3 h · Battery: LiFePO₄



Charging time: 20 h



Supply: 220 - 240 V 50/60 Hz

LED

LED temperature: 4000 °K (6500 °K under request)



Glass diffuser:

- Lighting working temperature -20 °C to +55 °C
- Emergency working temperature: 0°C to +50°C


Polycarbonate diffuser:

- Lighting working temperature: -20 °C to +50 °C
- Emergency working temperature: 0 °C to +50 °C

AutoTest



DIMENSIONS (mm)



STANDARDS COMPLIANCE

EN-60598-2-22
AutoTest: EN-62034
DALI-2: EN 62386

CERTIFICATIONS



ClassNK



AutoTest & DALI-2 Lithium



RANGE

LIGHTING

Dimensions	Polycarbonate Enclosure	Lighting	Communication
E1	LSIPC1100	1 300 lm	
E1	LSIPC1200	2 500 lm	
E2	LSIPC2200	2 650 lm	
E2	LSIPC22005	2 650 lm	
E2	LSIPC2200A	2 650 lm	DALI-2
E2	LSIPC2400	5 000 lm	
E3	LSIPC3110	11 750 lm	
E3	LSIPC3110A	11 750 lm	DALI-2
E3	LSIPC3400	5 000 lm	
E3	LSIPC34005	5 000 lm	
E3	LSIPC3400A	5 000 lm	DALI-2

Dimensions	Glass Enclosure	Lighting	Communication
E1	LSIVC1100	1 300 lm	
E1	LSIVC1200	2 500 lm	
E2	LSIVC2200	2 650 lm	
E2	LSIVC22005	2 650 lm	
E2	LSIVC2200A	2 650 lm	DALI-2
E2	LSIVC2400	5 000 lm	
E3	LSIVC3110	11 750 lm	
E3	LSIVC3110A	11 750 lm	DALI-2
E3	LSIVC3400	5 000 lm	
E3	LSIVC34005	5 000 lm	
E3	LSIVC3400A	5 000 lm	DALI-2

References ending in 5 are for through-wiring.

CASAMBI
(under request)

ClassNK



ZEMPER

EMERGENCY - Polycarbonate Enclosure

Dimensions	Type*	Enclosure	Emergency	Lighting	Battery	Duration	Communication
E1	NM	LSPC3045LX	45 lm		3.2V 0.5Ah LiFePO ₄	1h	AUTOTEST (SATI NF)
E1	NM	LSPC3400LX	430 lm		3.2V 1.8Ah LiFePO ₄	1h	AUTOTEST (SATI NF)
E1	M/NM	LSPC1700LXP	750 lm	2150 lm	3.2V 3.0Ah LiFePO ₄	1h	AUTOTEST
E2	M/NM	LSPC2400LAP	750 lm	2500 lm	3.2V 3.0Ah LiFePO ₄	1h	DALI-2
E2	M/NM	LSPC2400LXP	750 lm	2500 lm	3.2V 3.0Ah LiFePO ₄	1h	AUTOTEST
E2	NM	LSPC2700LX	750 lm		3.2V 3.0Ah LiFePO ₄	1h	AUTOTEST
E2	M/NM	LSPC2700LXP	750 lm	4750 lm	3.2V 3.0Ah LiFePO ₄	1h	AUTOTEST
E2	M/NM	LSPC2700LAP	750 lm	4750 lm	3.2V 3.0Ah LiFePO ₄	1h	DALI-2
E3	M/NM	LSPC3700LAP	750 lm	4750 lm	3.2V 3.0Ah LiFePO ₄	1h	DALI-2
E3	M/NM	LSPC3700LXP	750 lm	4750 lm	3.2V 3.0Ah LiFePO ₄	1h	AUTOTEST
E1	NM	LSPC1400LX3	350 lm		3.2V 6.0Ah LiFePO ₄	3h	AUTOTEST
E1	NM	LSPC1700LX3	750 lm		3.2 V 9.0Ah LiFePO ₄	3h	AUTOTEST
E2	M/NM	LSPC2400LAP3	750 lm	2500 lm	3.2 V 9.0Ah LiFePO ₄	3h	DALI-2
E2	M/NM	LSPC2400LXP3	750 lm	2500 lm	3.2 V 9.0Ah LiFePO ₄	3h	AUTOTEST
E2	M/NM	LSPC2700LAP3	750 lm	4750 lm	3.2 V 9.0Ah LiFePO ₄	3h	DALI-2
E2	NM	LSPC2700LX3	750 lm		3.2 V 9.0Ah LiFePO ₄	3h	AUTOTEST
E2	M/NM	LSPC2700LXP3	750 lm	4750 lm	3.2 V 9.0Ah LiFePO ₄	3h	AUTOTEST
E3	M/NM	LSPC3700LAP3	750 lm	4750 lm	3.2 V 9.0Ah LiFePO ₄	3h	DALI-2
E3	M/NM	LSPC3700LXP3	750 lm	4750 lm	3.2 V 9.0Ah LiFePO ₄	3h	AUTOTEST

EMERGENCY - Glass Enclosure

Dimensions	Type*	Enclosure	Emergency	Lighting	Battery	Duration	Communication
E1	NM	LSVC3045LX	45 lm		3.2V 0.5Ah LiFePO ₄	1h	AUTOTEST (SATI NF)
E1	NM	LSVC3400LX	430 lm		3.2V 1.8Ah LiFePO ₄	1h	AUTOTEST (SATI NF)
E1	M/NM	LSVC1700LXP	800 lm	2500 lm	3.2V 3.0Ah LiFePO ₄	1h	AUTOTEST
E2	M/NM	LSVC2400LAP	800 lm	2650 lm	3.2V 3.0Ah LiFePO ₄	1h	DALI-2
E2	M/NM	LSVC2400LXP	800 lm	2650 lm	3.2V 3.0Ah LiFePO ₄	1h	AUTOTEST
E2	M/NM	LSVC2700LAP	800 lm	5000 lm	3.2V 3.0Ah LiFePO ₄	1h	DALI-2
E2	NM	LSVC2700LX	800 lm		3.2V 3.0Ah LiFePO ₄	1h	AUTOTEST
E2	M/NM	LSVC2700LXP	800 lm	5000 lm	3.2V 3.0Ah LiFePO ₄	1h	AUTOTEST
E3	M/NM	LSVC3700LAP	800 lm	5000 lm	3.2V 3.0Ah LiFePO ₄	1h	DALI-2
E3	M/NM	LSVC3700LXP	800 lm	5000 lm	3.2V 3.0Ah LiFePO ₄	1h	AUTOTEST
E1	NM	LSVC1400LX3	400 lm		3.2V 6.0Ah LiFePO ₄	3h	AUTOTEST
E1	NM	LSVC1700LX3	800 lm		3.2 V 9.0Ah LiFePO ₄	3h	AUTOTEST
E2	M/NM	LSVC2400LAP3	800 lm	2650 lm	3.2 V 9.0Ah LiFePO ₄	3h	DALI-2
E2	M/NM	LSVC2400LXP3	800 lm	2650 lm	3.2 V 9.0Ah LiFePO ₄	3h	AUTOTEST
E2	M/NM	LSVC2700LAP3	800 lm	5000 lm	3.2 V 9.0Ah LiFePO ₄	3h	DALI-2
E2	NM	LSVC2700LX3	800 lm		3.2 V 9.0Ah LiFePO ₄	3h	AUTOTEST
E2	M/NM	LSVC2700LXP3	800 lm	5000 lm	3.2 V 9.0Ah LiFePO ₄	3h	AUTOTEST
E3	M/NM	LSVC3700LAP3	800 lm	5000 lm	3.2 V 9.0Ah LiFePO ₄	3h	DALI-2
E3	M/NM	LSVC3700LXP3	800 lm	5000 lm	3.2 V 9.0Ah LiFePO ₄	3h	AUTOTEST

*NM: Non-maintained. The luminaire operates from emergency supply only upon failure of the normal mains supply.

*M/NM: Maintained/Non-maintained. With a third terminal which allows to switch off/on the Maintained mode when connected to mains supply.

SPACING TABLE

EMERGENCY (Polycarbonate Enclosure)

LSPC1700LX3 = 750 lm

Mounting Height	0.5 lux				1 lux			
2.0 m	5.14 m	12.79 m	9.92 m	4.05 m	5.14 m	12.79 m	9.92 m	4.05 m
2.5 m	6.43 m	16.00 m	12.37 m	5.05 m	5.98 m	14.95 m	11.56 m	4.77 m
3.0 m	7.72 m	19.20 m	14.84 m	6.06 m	6.35 m	16.00 m	12.47 m	5.18 m
3.5 m	8.38 m	20.98 m	16.29 m	6.71 m	6.65 m	16.88 m	13.43 m	5.52 m
4.0 m	8.76 m	22.07 m	17.14 m	7.13 m	6.90 m	17.64 m	14.27 m	5.80 m
4.5 m	9.09 m	23.01 m	18.16 m	7.50 m	7.10 m	18.30 m	15.02 m	6.00 m

EMERGENCY (Glass Enclosure)


LSVC1700LX3 = 800 lm

Mounting Height	0.5 lux				1 lux			
2.0 m	4.71 m	11.85 m	9.65 m	4.06 m	4.71 m	11.85 m	9.65 m	4.06 m
2.5 m	5.87 m	14.78 m	12.01 m	5.05 m	5.87 m	14.78 m	12.01 m	5.05 m
3.0 m	7.05 m	17.74 m	14.42 m	6.06 m	6.25 m	15.76 m	13.18 m	5.51 m
3.5 m	8.22 m	20.70 m	16.82 m	7.07 m	6.60 m	16.59 m	14.23 m	5.89 m
4.0 m	8.65 m	21.79 m	18.11 m	7.59 m	6.91 m	17.30 m	15.18 m	6.18 m
4.5 m	9.03 m	22.70 m	19.19 m	8.00 m	7.19 m	18.06 m	16.03 m	6.43 m

PHOTOMETRIC GUIDE


Polycarbonate Enclosure

LSPC1700LX3 = 750 lm



Glass Enclosure

LSPVC1700LX3 = 800 lm



For further photometric data or spacing tables, please contact us.

ACCESSORIES *



CAM001
Ringbolt for
suspended mounting



BRD001
Flange for surface
ceiling mounting



APS600
(under request)



PSA001
Cable gland

(*) not included with the luminaires



Entirely designed and
manufactured in **Spain**



The Zemper Way to a Better World

We use recycled paper in the production of our catalogues, thus contributing to the conservation of forests and biodiversity. This paper requires up to 50% less energy and 90% less water, which significantly reduces environmental impact, reduces carbon dioxide emissions and promotes the circular economy. The ink we use is free of mineral oils, cobalt salts and VOCs (volatile organic compounds) so we contribute to limiting the environmental impact. We make more sustainable decisions and help protect our Planet.

ZEMPER

THE EMERGENCY LIGHTING SPECIALIST

Zemper Spain

Avda. de la Ciencia, 3 · Pol. Industrial Avanzado
13005 Ciudad Real (Spain)
Tel. +34 **926 271 837** · export@zemper.com

Zemper BeLux

Baronstraat 122
8870 IZEGEM · Bélgica
Tel. +32 51 800 210
belux@zemper.com

Zemper France

ZA des Berthilliers
189 Chemin des Frozières
71850 Charnay-lès-Mâcon · Francia
Tel. +33 3 85 34 66 20
commercial@zemperfrance.com

Zemper UK

Thornhill House, Thornhill Road,
Solihull, B91 2HB
Tel. +44 (0)121 703 2867
hello@zemper.co.uk

Commercial Offices

Marruecos
marruc@zemper.com
Colombia
export@zemper.com

www.zemper.com