

## SMARTZ CONTROL UNIT+ UPS

CSZ003 SmartZ Alioth.

Taric 9405114090



### Certifications



### Functional Specifications

	Control Center
	Control system: Wireless SmartZ®
	Data Bus: Yes
	Supply: 5Vcc <3.0W
	Maintained mode consumption: 3.0W
	Charging time: 24 h

### Mechanical and Aesthetic Specifications

	Mounting: DIN Rail
	Insulation: Class III
	Body material: Sheet Iron
	Finish: Black RAL9005
	Working temperature: 0 / 40 °C
	Suitable for flammable surface: Yes



## SMARTZ CONTROL UNIT+ UPS CSZ003

### Installation characteristics

Battery: With uninterruptible power supply (INCLUDED)

- Power supply: 230V 50Hz
- Battery: 6.4V-1.5Ah LFP
- Duration: 2 h

Mounting: Wall mounted / DIN rail

Interfaces:

- 1 x RJ45 (Ethernet)
- 3 x USB 2.0
- 2 x HDMI
- 1 x USB C Power

Connectivity by Ethernet, Wi fi or SIM card

Client-Server Architecture (Webserver).



### Operating characteristics

Backup battery operation with additional accessory.

Possibility of loading installation plans.

Multiple test programming configurations, such as annual test duration.

Multiple operating modes (luminaires, installation).

Adaptive design. Multi-interface display (tablets, smartphones, laptops, PC).

Remote control without any extra module (Ethernet).

Automatic updates (plans, databases, firmware, etc.) via Ethernet or USB connection.

Exportable event log and test results.

Sending of configurable fault list by email.

Possibility of working with multiple languages.

Advanced configuration options (Maintenance date, configuration of digital inputs and outputs, etc.).

Operating frequency: 2.4 GHz.

Graphic interface that shows the status of the devices in real time.

### Accessories



CSZ003  
SMARTZ CONTROL UNIT+ UPS  
CSZ002+SAI002



B SZ01  
SMARTZ SIGNAL AMPLIFIER  
IP42/IK04 WHITE

# SMARTZ CONTROL UNIT+ UPS CSZ003

## Weight (kg)



Product weight:

0.78 kg

Boxed product weight:

0.89 kg

Weight of box of 6 units:

5.76 kg

## Dimensions (mm)

